



Head Diameter d2 max.	M2	M2.5	M3	M3.5	M4	M5	M6	M8
Pan Pozidriv® Type C		5.00	6.00		8.00	10.00	12.00	
Cheese Pozidriv®		4.50	5.50	6.00	7.00	8.50	10.00	
Flat Pozidriv® Type M		4.70	5.60		7.50	9.20	11.00	
Hex Washer Type D					8.90	10.40	13.00	17.00
6 Lobe Pan Type C	4.00	5.00	6.00		8.00	10.00	12.00	16.00
6 Lobe/Slot Pan			6.00		8.00			
6 Lobe Flat Type M	3.80	4.70	5.60		7.50	9.20	11.00	14.50

Head Height k max.	M2	M2.5	M3	M3.5	M4	M5	M6	M8
Pan Pozidriv® Type C		2.12	2.52		3.25	3.95	4.75	
Cheese Pozidriv®		1.90	2.30	2.70	2.90	3.70	4.30	
Flat Pozidriv® Type M		1.50	1.65		2.20	2.50	3.00	
Hex Washer Type D					4.23	5.25	6.25	8.35
6 Lobe Pan Type C	1.72	2.12	2.52		3.25	3.95	4.75	6.15
6 Lobe/Slot Pan			2.52		3.25			
6 Lobe Flat Type M	1.20	1.50	1.65		2.20	2.50	3.00	4.00

Driver Size / WAF (s)	M2	M2.5	M3	M3.5	M4	M5	M6	M8
Pan Pozidriv® Type C		1	1		2	2	3	
Cheese Pozidriv®		1	1	2	2	2	3	
Flat Pozidriv® Type M		1	1		2	2	3	
Hex Washer Type D					7	8	10	13
6 Lobe Pan Type C	X6	X8	X10		X20	X25	X30	X40
6 Lobe/Slot Pan			X10		X20			
6 Lobe Flat Type M	X6	X8	X10		X20	X25	X30	X40

Penetration Depth / Washer Thickness	M2		M2.5		M3		M3.5		M4		M5		M6		M8	
	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.
Pan Pozidriv® Type C			1.27	1.52	1.68	1.93			1.90	2.38	2.64	3.10	3.02	3.48		
Cheese Pozidriv®			1.10	1.35	1.60	1.85	1.50	1.75	1.90	2.35	2.30	2.75	2.50	2.97		
Flat Pozidriv® Type M			1.22	1.47	1.48	1.73			1.60	2.06	2.05	2.51	2.46	2.92		
Hex Washer Type D									0.65		0.80		1.05		1.35	
6 Lobe Pan Type C		0.80		1.20		1.30				1.80		2.00		2.40		3.30
6 Lobe/Slot Pan						1.20				1.90						
6 Lobe/Slot Pan (Slot)						0.60				1.00						
6 Lobe Flat Type M		0.70		1.00		1.00				1.40		1.50		1.90		3.30

FOR MORE DETAILED INFORMATION, PLEASE REFER TO BOSSARD BN 2723, 2724, 3326, 3327, 11288, 13916, 14551 WHICH ARE THE GOVERNING STANDARDS

©2016 BY BOSSARD - LFG 10/01/2016