

DIN 128 A Curved Spring Lock Washers



DIN 128 A Curved Spring Lock Washers are intended to be used with short bolts primarily subjected to thrust forces and may be used with both right-hand and left-hand threads.

NOTE: DIN 128 A is recommended for new designs in place of DIN 127 A, DIN 127 B and DIN 128 B.

Nominal Size	ID min.	OD max.	Material Thickness	Washer Thickness min.
M2	2.1	4.4	0.5	0.7
M2.5	2.6	5.1	0.6	0.9
M3	3.1	6.2	0.7	1.1
M3.5	3.6	6.7	0.7	1.1
M4	4.1	7.6	0.8	1.2
M5	5.1	9.2	1	1.5
M6	6.1	11.8	1.3	2
M8	8.1	14.8	1.6	2.45
M10	10.2	18.1	1.8	2.85
M12	12.2	21.1	2.1	3.35
M14	14.2	24.1	2.4	3.9
M16	16.2	27.4	2.8	4.5
M18	18.2	29.4	2.8	4.5
M20	20.2	33.6	3.2	5.1
M22	22.5	35.9	3.2	5.1
M24	24.5	40	4	6.5
M27	27.5	43	4	6.5

All dimensions are in millimeters (mm). A decimal point instead of a comma is used as the decimal marker.

For informational purposes only.