


ISO 8752 Slotted Spring Pins Heavy Duty



Both ends are chamfered on pins less than 10 mm in diameter; only one end may be chamfered on 10 mm and larger diameter pins. Measure length from end to end. ISO 8752 is similar to DIN 1481. Also known as Roll Pins. Mounting hole nominal diameter tolerance zone is H12.

Nominal Size	Outside Diameter min.	Inside Diameter approx.	Chamfer Length min.	Wall Thickness nom.
1	1.2	0.8	0.15	0.2
1.5	1.7	1.1	0.25	0.3
2	2.3	1.5	0.35	0.4
2.5	2.8	1.8	0.4	0.5
3	3.3	2.1	0.5	0.6
3.5	3.8	2.3	0.6	0.75
4	4.4	2.8	0.65	0.8
4.5	4.9	2.9	0.8	1
5	5.4	3.4	0.9	1
6	6.4	4	1.2	1.2
8	8.5	5.5	1.6	1.5
10	10.5	6.5	2	2
12	12.5	7.5	2	2.5
13	13.5	8.5	2	2.5
14	14.5	8.5	2	3
16	16.5	10.5	2	3
18	18.5	11.5	2	3.5
20	20.5	12.5	3	4

All dimensions are in millimeters (mm). A decimal point instead of a comma is used as the decimal marker.

For informational purposes only.